




XCR- Series Motorhome Chassis

<u>FEATURE</u>	<u>BENEFIT</u>
■ 3 Year, 50,000 Mile Warranty	Best in The Industry
■ 50,000 PSI Frame Rail	Solid Foundation
■ 60 Degree Wheel Cut	Excellent Maneuverability
■ 400 Dealers	Service Where You Need It

2008 MODEL YEAR



40' Allegro Bus

by Tiffin

40' Allegro Bus by Tiffin Custom Chassis Features

- 5 year, 100,000 mile coolant ***
 - TranSynd Transmission Fluid
 - Lowered engine
 - 18.7 CFM air compressor
 - Fuel/water separator
 - Farr Eco air cleaner
 - Air filter restriction indicator
 - 1,000 watt in-block engine heater
 - Compression Brake by Jacobs (3,6)
 - R-134A air conditioning compressor
 - Electronic cruise control with high idle
 - VIP *Smart Wheel*, 18 in (457mm)
 - TRW infinitely adjustable tilt/
telescoping steering column
 - Suspended & adjustable pedals
 - Push button shift control
 - Driver message center with intergral
LCD display
 - 5" gauge package
 - Air ride suspension with custom
tuned Sachs shocks
 - 295/80R 22.5 LRH
 - Polished aluminum wheels with trim
kit
 - Heater hose assembly to front of
chassis
 - Haldex PURest heated air dryer
 - Automatic, heated moisture ejector
 - Air suspension deflation system
 - Day Time Running Lights
 - Tow power connector
- * Towing capacity limited by towing components and their attachment to the frame. See operators manual for braking requirements on towed vehicles
- *** Some maintenance required

For reference only. For certified dimensions, consult Freightliner Custom Chassis Corporation. Specifications are as of 4/05/07, and are subject to change without notice. Ratings are general guidelines. Illustrations may include optional equipment and accessories but may not include all standard equipment. To order more sales literature call 1-800-585-8831.



XCR-SERIES

Engine Peak Hp Peak Torque	Cummins ISL turbocharged, aftercooled, 8.9 L electronic diesel 425 Hp @ 2,200 rpm 1200 lb•ft (1627 N•m) @ 1,300 rpm
Transmission Gear Ratios:	Allison 3000MH six-speed automatic with lock up <u>First:</u> <u>Second:</u> <u>Third:</u> <u>Fourth:</u> <u>Fifth:</u> <u>Sixth:</u> <u>Rev:</u> 3.49:1 1.86:1 1.41:1 1.00:1 .75:1 .65:1 5.03:1
Vehicle Weight Ratings Front GAWR Rear GAWR GVWR GCWR *	14,600 lb (6628 kg) 20,000 lb (9080 kg) 34,600 lb (15 708 kg) 44,600 lb (20 248 kg)
Wheelbase	276 in (7010 mm)
Front Axle Capacity Track Width	ZF - RL67EM IFS 14,600 lb (6628 kg) 84.3 in (2141 mm)
Rear Axle Drive Ratio Capacity Track Width	4.63:1 20,000 lb (9080 kg) 72.1 in (1830 mm)
Brakes Front Service Rear Service Parking Rear	Full air brakes with ABS 17 in. Discs 16.5 x 7 in. drum- S-cam 16.5 x 7 in. drum Spring-applied air release
Cooling System Radiator Core Radiator Type Charge Air Cooler Transmission Oil Cooler Fan	2 rows, 14 FPI 1,260 in ² (8129 cm ²) area Cross-flow, side mounted Cross-flow, side mounted Water-to-oil Variable speed, hydraulic
Electrical System Alternator Starting Battery	Leece-Neville 170 amp Delco 41MT, 12 volt Two 950 CCA @ 0°F (-18°C); maintenance-free
Frame Max Resist. Bending Moment Max Frame Section	Raised Frame Rail with Lowered Rear Section 291,000 lb•in (32 892 N•m) 9.00 x 2.75 x .25 in (229 x 70 x 6.4 mm)
Fuel Tank	150 gal (568 L), dual fuel fill
Steering System Rating Ratio Wheel Cut	ZF - 8018 14,600 lb (6628 kg) 19.3:1 to 22.7:1 60°
Suspension Shock Absorber	ZF - RL67EM IFS air (front) Neway ADL air (rear) Custom Tuned Sachs shock absorbers
Tires	295/80R 22.5 LRH
Wheels	4 aluminum, 2 steel 22.5 x 8.25 in (572x210mm) with 10 bolt lugs 11.25 in (285.75 mm) diameter bolt center
Instrumentation	Gauges: Speedometer • Tachometer • Engine Oil Pressure • Water Temperature • Voltmeter • Fuel Level • Dual Air Pressure